
NCM 100SS PROFILE






IDEAL APPLICATION COMMERCIAL & RESIDENTIAL



Quality materials and more than 100 years of successful design application govern the construction of our NCM 100SS 1" mechanically seamed metal roof system. Ideal for light commercial or residential applications, this smartly detailed profile can be curved for enhanced architectural appeal. Installed as fulllength panels with no end laps helps provide the ultimate in allweather and watertight protection curved installations.



325 Duffy Ave // Hicksville, NY 11801 // Phone: 516.207.7708 // www.newcastlemetal.com // email: metalsales@ncmetal.com

©2025 New Castle. Inc. All rights reserved. Galvalume® is a registered trademark of BEIC International, Inc. Drexlume[™] is a trademark of Drexel Metals, Inc. ENERGY STAR name and logo are registered U.S. marks and are owned by the U.S. government. Colors shown represent the actual color as closely as possible. To ensure exact color final approval, a metal color chip is available. Warranty statements mentioned are outlines: complete Limited Warranty information is available on request. No other warranty expressed or implied is applicable.



NCM 100SS PROFILE



valspar

AVAILABLE WIDTHS 12", 14", 15", 16", 17", 18", 19", 20" or 21"

SUBSTRATES AVAILABLE

Galvalume® 24ga and 26ga Drexlume® - 24ga and 26 ga Aluminum .032" Copper 16 oz and lead-coated copper

PROFILE OPTIONS

- Single lock panel
- Double lock panel
- Radius panel (single or double lock)

FINISHES AND PRODUCT WARRANTY:

Available in a variety of coatings and colors by Valspar. See the New Castle Metals color card for standard colors and paint specifications.

GALVALUME® SUBSTRATE - 35 YEAR WARRANTY

35 YEAR NON PRO-RATED PVDF PAINT WARRANTY Highperformance painted metal roofing product, carefully tensioned leveled for superior flatness.

ALUMINUM SUBSTRATE - 35 YEAR WARRANTY

35 YEAR NON PRO-RATED PVDF PAINT WARRANTY Highperformance painted metal roofing product, carefully tensioned leveled for superior flatness.

DREXLUME® SUBSTRATE - 25 YEAR WARRANTY

Mill finished Galvalume® with a two-sided, clear acrylic finish.

PRODUCTION OPTIONS

Factory made or field rolled to exact lengths Optional: striation, beads, pencil ribs

INSTALLATION

Can be installed over plywood decking and New Castle Metals underlayment.

SLOPE


Minimum slope 2:12

MINIMUM ROOF PITCH

2:12 - low roof pitch

TESTING

- UL 580 Wind Uplift (Class 90)
- UL 2218 Class 4 Hail Impact
- · UL 790 Class A Fire Rating
- · UL Environmental -SRI Third Party Verified



Unseamed panel

Double lock panel



Testing in accordance with



